



Inline Cable Colour Code	Connector Specifications	Material Specifications	Dimensions in mm. Threads in inches. 1 inch = 25.4 mm. 1 mm = 0,3937 inch.
1 Black 2 White 3 Red 4 Green 5 Orange 6 Blue 7 White/Black 8 Red/Black 9 Green/Black 10 Orange/Black 11 Blue/black 12 Black/White 13 Red/White 14 Green/White 15 Blue/White 16 Black/Red	Single Contact Rating : 300 V @ 5 Amp Connector Rating 2-16 pins : 300 V @ 5 Amp Insulation Resistance : >200 megaohm Contact Resistance : >0,01 ohm Wet Matings : >500 Temp. Rating : -4° to +60° C - 25° to 140° F Depth Rating : 700 bar - 10.000 psi	Connector Body : Neoprene (CR) Bulkhead Body : Brass UNS-C36000 Contacts : Beryllium Copper UNS-C17300 Nuts & Washers : Brass UNS-C36000 'O' Rings : Nitrile Locking Sleeve : Delrin Snap Ring : AISI 302 Inline Cable (60 cm) : 20 AWG 0,5 mm <sup>2</sup> Rubber BH Leads (30 cm) : 20 AWG 0,5 mm <sup>2</sup> Teflon Options : See index pages	Drawing No. SE 300-71
(Bulkhead Leads Number Tagged)			Modification rights reserved