



Inline Cable Colour Code

- | | |
|---------------|-----------------|
| 1 Black | 9 Green/Black |
| 2 White | 10 Orange/Black |
| 3 Red | 11 Blue/Black |
| 4 Green | 12 Black/White |
| 5 Orange | 13 Red/White |
| 6 Blue | 14 Green/White |
| 7 White/Black | 15 Blue/White |
| 8 Red/Black | 16 Black/Red |

(Bulkhead Leads Number Tagged)

Connector Specifications

- | | |
|-----------------------------|------------------------------------|
| Single Contact Rating | : 600 V @ 15 Amp |
| Connector Rating 2-4 pins | : 600 V @ 10 Amp |
| Connector Rating 5-10 pins | : 600 V @ 6 Amp |
| Connector Rating 12-16 pins | : 600 V @ 5 Amp |
| Insulation Resistance | : >200 megaohm |
| Contact Resistance | : <0,01 ohm |
| Wet Matings | : >500 |
| Temp. Rating | : -4° to +60° C -
25° to 140° F |
| Depth Rating | : 1.400 bar - 20.000 psi |

Material Specifications

- | | |
|----------------------|-------------------------------------|
| Connector Body | : Neoprene (CR) |
| Bulkhead Body | : AISI 316 |
| Contacts | : Brass UNS-C36000 |
| Nuts & Washers | : AISI 316 |
| 'O' Rings | : Nitrile |
| Locking Sleeve | : Delrin |
| Snap Ring | : AISI 302 |
| Inline Cable (60 cm) | : 18 AWG 1,0 mm ² Rubber |
| BH Leads (30 cm) | : 18 AWG 1,0 mm ² Teflon |
| Options | : See index pages |

Dimensions in mm.
Threads in inches.
1 inch = 25,4 mm.
1 mm = 0,3937 inch.

Modification rights reserved

Drawing No. SE 300-10